AD-A259 09	6				(1)	
	MENTATIO	N PAGE			Form Approved OMB No. 0704-0188	
1a. F Und		16. RESTRICTIVE	MARKINGS			
2a. SECURITY CLASSIFICATION AUTHORITY		3 . DISTRIBUTION/AVAILABILITY OF REPORT				
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE		Unlimited				
4. PERFORMING ORGANIZATION REPORT NUMBER(S)		5. MONITORING ORGANIZATION REPORT NUMBER(S)				
DOD POP HMTR/AYD 91-003	DTIC					
6a. NAME OF PERFORMING ORGANIZATION	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MO	ONITORING ORGAN	ELE	CTE -	
Packaging Division, AED	SMCAR-AEP			DEC.1	A 1992°	
U.S. Army, ARDEC Picatinny Arsenal, NJ 07806-5000		7b. ADDRESS (City, State, and Code)				
8a. NAME OF FUNDING/SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT	T INSTRUMENT IDE	NTIFICAT	ION NUMBER	
8c. ADDRESS (City, State, and ZIP Code)			UNDING NUMBER			
		PROGRAM ELEMENT NO.	PROJECT NO.	NO.	WORK UNIT ACCESSION NO.	
11. TITLE (Include Security Classification)	_	_				
Performance Oriented Packaging Report for Charge, Demolition Block, 1/4 Pound, (TNT) w/ Priming Adapters M1A4						
12. PERSONAL AUTHOR(S)	apoolo illii					
Sniezek, Frank 13a. TYPE OF REPORT 13b. TIME CO	OVERED TO	14. DATE OF REPO	DT (Von Month I	200 115	. PAGE COUNT	
Final FROM	TO	92-11-0	, ,	13	. PAGE COUNT	
16. SUPPLEMENTARY NOTATION						
17. COSATI CODES		(Continue on reverse if necessary and identify by block number)				
FIELD GROUP SUB-GROUP Performance Oriented Packaging, POP, Charge, Demolition Block, 1/4 Pound, (TNT)						
	w/ Priming Adapters, Mil-B-2427 wood box					
19. ABSTRACT (Continue on reverse if necessary and identify by block number)						
This POP report is for the Charge, Demolition Block, 1/4 Pound, (TNT) w/ Priming Adapters which is packaged 192 charges/Mil-B-2427 wood box. This						
report describes the results of testing conducted on a similar packaging which is used as an analogy for this item.						
					+	
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT	21. ABSTRACT SECURITY CLASSIFICATION					
UNCLASSIFIED/UNLIMITED SAME AS R	Unclassified 22b. TELEPHONE (Include Area Code) 22c. OFFICE SYMBOL					
22a. NAME OF RESPONSIBLE INDIVIDUAL STEVE RUFFINI		(201) 724-2		SMCAR		

I. REPORT NUMBER: DOD POP HMTR/AYD 91-003

II. TITLE: Performance Oriented Packaging Report for Charge, Demolition Block, 1/4 Pound, (TNT) w/ Priming Adapters M1A4

AUTHOR: Frank M. Sniezek

PERFORMING ACTIVITY: ARDEC

ADDRESS: Department of the Army

ARDEC, SMCAR-AEP

HQ, U.S. Army Armament, Munitions, and Chemical Command

Picatinny Arsenal, NJ 07806-5000

DATE: 2 Nov 92

Approved for public release; Distribution is unlimited

ಮಿಸಿನಲ್ ಜ್ಞಾಲಕಾಲ್ಯತ್ತದೆ ಸಾಚಿಕ್ಷಾ ಕಾಲಕಿಕ್ಕಾಗಿ ಸ

92 12 11 030

Acee	esion For	
NTIS		
Umani	scuneed	_
ByDistr	flution/	_
Avai	lability Codes	_
Dist	Avail and/or Special	1
H-1		



1. DATA SHEET

CONTAINER

Type: Box UN Code: 4C1

Nomenclature: Packing and Marking for Charge, Demolition Block, 1/4

Pound, (TNT) w/ Priming Adapters M1A4

Specification Number: Type II, Grade A, Class 2, Mil-B-2427

Drawing Number: 8797739

Material: Wood

Gross Weight: 84.0 pounds

Outside Dimensions: $18 \times 16 = 5/8 \times 9 = 3/4 \text{ (P/N } 8797113)$

 $18 \ 1/4 \times 16 \ 7/8 \times 9 \ 3/4 \ (P/N \ 9287850)$

Inside Dimensions: 15 1/8 x 15 1/8 x 7 9/16 (P/N 8797113)

15 $3/8 \times 15 3/8 \times 7 9/16 (P/N 9287850)$

PRODUCT

Name: 1/4 Pound (TNT) w/ Priming Adapters M1A4

Drawing Number: 8757113 or 9287850

United Nations Number: 0048

Physical State: Solid

Amount per Container: 192 Charge, Demolition Block, 1/4 lb, (TNT) w/

48 Priming Adapters M1A4

2. BACKGROUND, TESTS, AND RESULTS

Reference the following document:

a. 49CFR, October 1, 1991 Edition

Instead of testing the specific containers used for the 1/4 Pound Demolition Block Charges, three wooden boxes built to the same specification but packed with a fiberboard box loaded with sand were tested. The corresponding weight and dimensions of the tested box are as follows:

Gross Weight: 120 pounds

Outside Dimensions: $18 \frac{1}{4} \times 16 \frac{7}{8} \times 12 \frac{1}{4}$ Inside Dimensions: $15 \frac{3}{8} \times 15 \frac{3}{8} \times 9 \frac{3}{4}$

This falls within the guidelines for analogy IAW Variation III of para. 178.601(g)(3) of Reference a.

A Stacking Test was conducted on one container with a weight of 1200 pounds for 72 hours in lieu of three containers for 24 hours. This weight exceeds the minimum requirement for a 10 foot stack height which is 1176 pounds.

A Loose Cargo Test was conducted on three containers for one hour. The packages were tested at a vibration table frequency such that the bottom of the packages were raised 1/4 inch from the platform, which exceeds the requirement of 1/16 inch.

A Four Foot Drop Test was conducted on one of the containers that was subjected to the Loose Cargo Test. One container was dropped five times at different orientations as follows: top, bottom, long side, short side, and a top corner at the closure. This exceeds the requirement of one drop per container.

Test results indicated no leakage or spillage of the contents from the containers following any of the tests conducted meeting the requirements of the 49CFR.